



ISS Space Weather Needs*

- Solar activity/thermosphere density prediction and satellite torque/drag predictions for:
 - Mission planning and controllability/real-time operations
 - MM/OD environment evolution
- MSFC meteor storm severity predictions driven by the Perseids on Mir events of 12 August 1993
- Role of solar/geomagnetic activity/thermosphere in managing ISS crew ionizing radiation dose exposure
- ISS interaction with auroral particle precipitation why this isn't a problem or do we need forecasting?
- Monitor for changes in the SAA altitude structure and geographic extent for crew IR dose management
- Ionospheric Ne, Te values along ISS orbit for characterizing ISS charging hazards:
 - Near real time Ne, Te data
 - Well validated real time model Ne, Te output

^{*}from S. Koontz/ISS Environments Manager



Introduction

Overview

- Background
 - ISS interaction with plasma environment
 - Charging hazards to vehicle and crew
 - ISS Program hazard mitigation strategies
- ISS plasma environment monitoring
 - Floating Potential Measurement Unit (FPMU)
- CCMC CTIPe real time plasma model
 - Examples of success
 - Issues in work
- Summary and future needs

ISS/FPMU:	JSC	Steve Koontz (ISS Environments Lead), John Alred, Jack Bacon
	MSFC	Mike Chandler, Victoria Coffey, Joseph Minow, Paul Craven,
		Todd Schneider, Ken Wright (UAH)
	Boeing	Drew Hartman, Leonard Kramer, Ron Mikatarian, Danny Schmidl
CTIPe model:	NOAA	Tim Fuller-Rowell
CCMC team:	GSFC	Ja Soon Shim (UMBC/NASA), Lutz Rastaetter (NASA),
		Masha Kuznetsova (NASA)



ISS Structure Potential Variations and Hazards

ISS potential varies in low Earth orbit environment due to:

Current collection

Observed Voltage Ranges to Date

_	Current collection from ambient plasma
	4CO V LIC solor orroy

- 160 V US solar array
- Visiting vehicle (high voltage) solar arrays
- Operation of payloads that emit current sources

Inductive potentials

- (vxB).•L due to motion across geomagnetic field
- E.• L due to ionospheric electric fields
- Auroral electrons

-	0.1 to -0.5 volts
	-20 to -90 volts
	-10 volts

+10 to +25 volts

+/-40 volts

few volts -20 volts

- Hazards to vehicle and crew
 - ISS-EVA-305: long term degradation of thin dielectric surface thermal control coatings due to arcing ...EVA touch temp violations (eventually)
 - Hazard marginalized by test and analysis no controls needed
 - ISS-EVA-312: EVA electric shock
 - Hazard 1 Catastrophic at floating potentials more negative than -40V
 - Hazard 2 Critical to catastrophic at positive floating potentials (> 0V)
 - Hazard 3 critical to catastrophic ISS electrical power short through EVA crew to ground
 - Plasma is a secondary cause one circuit closure pathway



ISS Plasma Hazard Management

ISS Program controls plasma hazards through a process of active potential control, operational mitigation strategies, environment monitoring and characterization, and probabilistic risk assessment

Plasma Contactor Units (PCUs)

- Provides active ISS "ground" by dissipating surface charges to space
- Two redundant PCU units provides single fault failure tolerance, two required for EVA



- Manages solar array and magnetic induction charging
- Provides two fault tolerance


Floating Potential Measurement Unit (FPMU)

 Provides validated measurements of ISS floating potential and ionospheric Ne, Te along ISS orbit

Plasma Interaction Model (PIM)

- ISS charging model validated with FPMU data
- Predicts charging hazard severity and frequency of occurrence








Floating Potential Measurement Unit (FPMU)

FPP: Floating Potential Probe

WLP: Wide-sweep Langmuir Probe

NLP: Narrow-sweep Langmuir Probe

PIP: Plasma Impedance Probe



Role:

- Validation of PIM
- > Assess PV array variability
- > Interpreting IRI predictions
- > Characterize ISS charging


Sensor	Measured Parameter	Rate (Hz)	Effective Range
FPP	V _F	128	-180 V to +180 V
WLP	N T _e V _F	1	10 ⁹ m ⁻³ to 5·10 ¹² m ⁻³ 500 K to ~10000 K -20 V to 80 V
NLP	N T _e V _F	1	10 ⁹ m ⁻³ to 5·10 ¹² m ⁻³ 500 K to ~10000 K -180V to +180 V
PIP	N	512	1.1·10 ¹⁰ m ⁻³ to 4·10 ¹² m ⁻³

[Wright et al., 2008; Barjatya et al., 2009]





Characterizing ISS Environments, Charging





Alternative Ne, Te Data and/or Model Sources

We have in-situ FPMU Ne, Te measurements along ISS orbit...

- ...but we are interested in identifying independent Ne, Te data sources from both measurements and models appropriate for ISS altitudes
- FPMU validation against independent measurements, models
 - Incoherent scatter radar Ne, Te, ionosonde Ne, TIMED/GUVI Ne
 - IRI, GAIM model Ne, Te
- FPMU data unavailable during EVA, docking, and other operations with higher Ku band video downlink priority
 - Real time data, models may be useful to provide coverage during these periods
- FPMU operated on campaign basis (~25 to 30% of year)
 - Well validated models or alternate data sources can provide environment characterization data between FPMU runs
- Contingency planning in case of FPMU failure
 - Default to current "worst case" analysis for EVA planning...but that impacts ISS power availability
 - Alternative data, validated models could provide operations relief to power constraint





CCMC Real-time Ionosphere Ne, Te for ISS

Coupled Thermosphere Ionosphere Plasmasphere Electrodynamics (CTIPe) Model

- CCMC implemented real time CTIPe model in spring 2010 (CTIPe_RT) with output specific for ISS orbit
- ISS ephemeris from GSFC/SSCWeb
- New record every 10 minutes gives
 90 minutes of data at 5 sec time steps

CTIPe_at_ISS_20100909_192000.txt 09/09/2010 07:01PM # Data printout from CCMC-simulation: version 1.1 # Data type: CTIP ionosphere/thermosphere # Run name: 2010-09 Missing data: -1.100E+12									
# Coordinate System: GEO									
# fixed dipole tilt angles u	0.00000								
# Satellite Track: iss # Output data: field with 1x1081=1081 elements									
#YYYYMM DD HH MM Sec lo	on lat IP	N_e N_O+	N_H+ T_i T_	_e					
# year month day h m s [de	eg] [deg] [km]	[m^-3] [m^-3]	[m^-3] [K] [I	K]					
2010 09 09 17 50 0.000 254	1.4 -9.250 351.5	7.522E+11 7.501E+11	2.108E+09 1125. 182	28.					
2010 09 09 17 50 5.000 254	1.6 -8.994 351.5	7.494E+11 7.473E+11	2.089E+09 1125. 183	31.					
2010 09 09 17 50 10.000 254	1.8 -8.738 351.4	7.465E+11 7.444E+11	2.069E+09 1125. 183	34.					
2010 09 09 17 50 15.000 254	1.9 -8.483 351.4	7.434E+11 7.414E+11	2.050E+09 1125. 183	37.					
2010 09 09 17 50 20.000 255	5.1 -8.227 351.3	7.402E+11 7.382E+11	2.030E+09 1124. 184	40.					
2010 09 09 17 50 25.000 255	5.3 -7.971 351.3	7.366E+11 7.346E+11	2.010E+09 1124. 184	43.					
2010 09 09 17 50 30.000 255	5.5 -7.715 351.2	7.312E+11 7.292E+11	1.989E+09 1123. 184	44.					
2010 09 09 17 50 35.000 255	5.7 -7.459 351.1	7.259E+11 7.239E+11	1.968E+09 1122. 184	46.					
2010 09 09 17 50 40.000 255	5.9 -7.203 351.1	7.205E+11 7.186E+11	1.947E+09 1120. 184	48.					
2010 09 09 17 50 45.000 256	5.1 -6.947 351.0	7.151E+11 7.132E+11	1.927E+09 1119. 185	50.					
(records deleted)									
2010 09 09 19 20 0.000 227	7.5 -14.02 352.8	3.634E+11 3.621E+11	1.289E+09 989.1 173	10.					







Example CTIPe_RT Daily Output

CTIPe_RT output at CCMC:

Integrated Space Weather Analysis System (iSWA) http://iswa.gsfc.nasa.gov/iswa/iSWA.html


Anonymous ftp ftp://hanna.ccmc.gsfc.nasa.gov/

CTIPe Model Description:

http://ccmc.gsfc.nasa.gov/models/modelinfo.php?model=CTIPe


MSFC is evaluating CTIPe_RT for possible ISS ops use:

- Periodically download text output files and process into daily data sets retaining the unique records
- Compare CTIPe_RT Ne, Te with measurements from FPMU
- This is a work in progress, both for ISS and CCMC! Only preliminary results shown here...






CTIPe_RT Output and FPMU Survey Plot






Good CTIPe_RT/FPMU Comparison






Good CTIPe_RT/FPMU Comparison






Less Good CTIPe RT/FPMU Comparison





Poor CTIPe RT/FPMU Comparison






Incorrect CTIPe_RT ISS Ephemeris Issue

MSFC FPMU analysis software

 ISS ephemeris generated from NORAD TLE's using Satellite Tool Kit (STK) software is consistent with ISS/FPMU data

CCMC real time model


- CTIP output based on incorrect ISS ephemeris obtained from SSCWeb for complete 2010/165 – 168 ISR World Day campaign
- CCMC considering options for robust orbit generation tools for real time model support





Characterizing High Latitude Charging Environment


- ISS environments teams are investigating vehicle charging observed at eclipse exit
- CTIPE RT model confirmed physical origin of the plasma depletions for charging events observed at high latitudes, allows us to predict periods for studying charging phenomenon



joseph.i.minow@nasa.gov, GSFC SW and NASA Robotic Missions Workshop, 15 Sep 2010



FPMU Data Unavailable During EVA





Summary and Future Needs

- ISS Program currently using FPMU Ne, Te in-situ measurements to support operations and anomaly investigations
 - Working to acquire alternative data sources if FPMU is not available
- Work is progressing on CCMC tools for low Earth orbit ionosphere characterization
 - Validation against FPMU data required before model output can be used for ISS operational support
 - MSFC plans to continue comparing CTIP output during FPMU campaigns
 - Results to date have been useful in identifying ionospheric origins of high latitude charging environments
- CTIPe-RT model issues to be addressed before using output for ISS ops:
 - Accuracy initial evaluation showing discrepancies with FPMU data
 - Operational reliability
 24/7 availability to support ops
 orbit propagator issues (accuracy, availability)
- Preliminary results to date focused on model implementation
 - Forward work will emphasize quantitative CTIP, FPMU Ne, Te comparisons
 - CCMC personnel are very responsive in discussing options and addressing needs!
- Future needs:
 - Implement CTIPe RT output for ISR, ionosonde sites
 - Provide additional data for validating CTIP output
 - Support validation of real time data to supplement FPMU output
 - Implement assimilative ionosphere models (e.g., GAIM)
 - Models constrained by Ne, Te data better for operations support, anomaly investigations